Al Applications Lecture 4

Licenses and Openness

SUZUKI, Atsushi Jing WANG

Outline

Introduction

Degrees of Openness with Examples

What Does "Open" Mean?

Specific Examples of Release Stages

License Basics (For Source Code)

Model-Specific Licenses (Open-Weight Type)

Case Study: Separation of Rights Holders

Model Versions and License Differences Across Versions

Practical Guidelines and Caveats

Summary

Next Time

Introduction

In the last lecture, we defined the function represented by a neural network as **generally as possible**.

In the last lecture, we defined the function represented by a neural network as **generally as possible**.

The key points were:

 The architecture is the design information: a DAG structure, activation functions, and the edge-parameter mapping.

In the last lecture, we defined the function represented by a neural network as **generally as possible**.

The key points were:

- The architecture is the design information: a DAG structure, activation functions, and the edge-parameter mapping.
- A checkpoint contains the specific parameter values obtained through training.

In the last lecture, we defined the function represented by a neural network as **generally as possible**.

The key points were:

- The architecture is the design information: a DAG structure, activation functions, and the edge-parameter mapping.
- A checkpoint contains the specific parameter values obtained through training.
- Only with both the architecture $f_{(\cdot)}$ and the checkpoint θ is a **specific** function f_{θ} uniquely determined.

Let's revisit this perspective using mathematical notation.

Let's revisit this perspective using mathematical notation.

For an input space \mathcal{X} , an output space \mathcal{Y} , and a parameter space $\Theta \subset \mathbb{R}^D$:

Architecture
$$f_{(\cdot)}:\Theta \to \{\mathcal{X} \to \mathcal{Y}\}, \qquad \theta \in \Theta \mapsto f_{\theta}:\mathcal{X} \to \mathcal{Y}.$$

Let's revisit this perspective using mathematical notation.

For an input space \mathcal{X} , an output space \mathcal{Y} , and a parameter space $\Theta \subset \mathbb{R}^D$:

Architecture
$$f_{(\cdot)}:\Theta \to \{\mathcal{X} \to \mathcal{Y}\}, \qquad \theta \in \Theta \mapsto f_{\theta}:\mathcal{X} \to \mathcal{Y}.$$

- **Training** is determining parameters θ^* based on data.
- **Inference** is applying the final function f_{θ^*} .

1.2 Learning Outcomes

By the end of this lecture, students should be able to explain and judge the following:

1.2 Learning Outcomes

By the end of this lecture, students should be able to explain and judge the following:

 Systematically explain the various stages of releasing and licensing a neural network model.

1.2 Learning Outcomes

By the end of this lecture, students should be able to explain and judge the following:

- Systematically explain the various stages of releasing and licensing a neural network model.
- Determine whether a model provided under an Open Source Software
 (OSS) license can be used for their own purposes, by referencing major licenses.

Remark (Important Disclaimer)

The speaker of this lecture is not a legal expert. The content presented here is **general guidance**.

Remark (Important Disclaimer)

The speaker of this lecture is not a legal expert. The content presented here is **general guidance**.

 For specific cases, you must consult with lawyers in your respective country and region.

Remark (Important Disclaimer)

The speaker of this lecture is not a legal expert. The content presented here is **general guidance**.

- For specific cases, you must consult with lawyers in your respective country and region.
- The goal is to **reasonably prevent** legal risks.

Remark (Important Disclaimer)

The speaker of this lecture is not a legal expert. The content presented here is **general guidance**.

- For specific cases, you must consult with lawyers in your respective country and region.
- The goal is to **reasonably prevent** legal risks.
- Final decisions should be made at your own responsibility. Refer to official documentation [1, 2, 3].

Degrees of Openness with

Examples

Neural networks span a spectrum from **completely closed** to **almost completely open**.

Neural networks span a spectrum from **completely closed** to **almost completely open**.

• Completely Closed: Only a User Interface (UI) or Application Programming Interface (API) is shared. You send inputs and get outputs, but see nothing else.

Neural networks span a spectrum from **completely closed** to **almost completely open**.

- Completely Closed: Only a User Interface (UI) or Application Programming Interface (API) is shared. You send inputs and get outputs, but see nothing else.
- Almost Open: Architecture, checkpoints, and even the training code or "recipes" are released.

Neural networks span a spectrum from **completely closed** to **almost completely open**.

- Completely Closed: Only a User Interface (UI) or Application Programming Interface (API) is shared. You send inputs and get outputs, but see nothing else.
- Almost Open: Architecture, checkpoints, and even the training code or "recipes" are released.
- A model's license determines if others can freely use it, regardless of how "open" it is.

Example (The Staged Release of GPT-2)

When OpenAl's GPT-2 was announced in 2019, the weights for the largest model were subject to a **staged release** due to safety concerns [4].

Example (The Staged Release of GPT-2)

When OpenAl's GPT-2 was announced in 2019, the weights for the largest model were subject to a **staged release** due to safety concerns [4].

• Initially, the most powerful 1.5B parameter model was completely closed.

Example (The Staged Release of GPT-2)

When OpenAl's GPT-2 was announced in 2019, the weights for the largest model were subject to a **staged release** due to safety concerns [4].

- Initially, the most powerful 1.5B parameter model was completely closed.
- The full model was eventually released in November 2019 after a period of study and debate [5].

Example (LLMs as a Service)

As of August 2025, OpenAl provides **ChatGPT-5** via its ChatGPT interface and API.

Example (LLMs as a Service)

As of August 2025, OpenAl provides **ChatGPT-5** via its ChatGPT interface and API.

· Inference is executed on their servers.

Example (LLMs as a Service)

As of August 2025, OpenAl provides **ChatGPT-5** via its ChatGPT interface and API.

- Inference is executed on their servers.
- The details of the architecture and checkpoints are generally not disclosed [6].
- Users only interact with prompts and outputs.

Example ("Open" Models and Distribution Platforms)

Models like Llama (Meta), Qwen (Alibaba), Mistral (Mistral AI), and DeepSeek (DeepSeek AI) are known as open (Open Weights/Open Model).

Example ("Open" Models and Distribution Platforms)

Models like Llama (Meta), Qwen (Alibaba), Mistral (Mistral AI), and DeepSeek (DeepSeek AI) are known as open (Open Weights/Open Model).

• The **Hugging Face Hub** is a major platform for their distribution [7].

Example ("Open" Models and Distribution Platforms)

Models like Llama (Meta), Qwen (Alibaba), Mistral (Mistral AI), and DeepSeek (DeepSeek AI) are known as open (Open Weights/Open Model).

- The **Hugging Face Hub** is a major platform for their distribution [7].
- You can download the architecture and checkpoints to run locally.

Example ("Open" Models and Distribution Platforms)

Models like Llama (Meta), Qwen (Alibaba), Mistral (Mistral AI), and DeepSeek (DeepSeek AI) are known as open (Open Weights/Open Model).

- The **Hugging Face Hub** is a major platform for their distribution [7].
- You can download the architecture and checkpoints to run locally.
- Licenses are (usually) clearly stated in the model repositories.
 [8, 9, 10, 11, 12]

What Does "Open" Mean?

3. What Does "Open" Mean?

Generally, when a model is called "open," it means that at a minimum, the following are publicly available:

3. What Does "Open" Mean?

Generally, when a model is called "open," it means that at a minimum, the following are publicly available:

• The **architecture** (as configuration files or code).

3. What Does "Open" Mean?

Generally, when a model is called "open," it means that at a minimum, the following are publicly available:

- The **architecture** (as configuration files or code).
- The trained **checkpoint** (the weights).

So, what is often not disclosed even for "open" models?

So, what is often not disclosed even for "open" models?

Typically, the private components are:

• The training data.

So, what is **often not disclosed** even for "open" models?

Typically, the private components are:

- The training data.
- The training algorithm (including the complete training recipe and scripts for reproduction).

Remark (Feasibility of Inference and Training)

With the architecture $f_{(\cdot)}$ and checkpoint θ , **inference** is possible.

Remark (Feasibility of Inference and Training)

With the architecture $f_{(\cdot)}$ and checkpoint θ , **inference** is possible.

However, **reproducing** the training (arriving at the exact same θ) is usually impossible unless the data, recipe, random seeds, etc., are identical.

Remark (Feasibility of Inference and Training)


With the architecture $f_{(\cdot)}$ and checkpoint θ , **inference** is possible.

However, **reproducing** the training (arriving at the exact same θ) is usually impossible unless the data, recipe, random seeds, etc., are identical.

Even with "open weights," if the **insights from the training process** are not disclosed, the reproducibility and potential for adaptation are limited.

3.1 Visualizing the Relationship

This diagram uses our framework to show what's typically open vs. private.



Specific Examples of Release

Stages

UI/API-only Release (Hosted)

UI/API-only Release (Hosted)

• Only an **inference service** is provided.

UI/API-only Release (Hosted)

- Only an **inference service** is provided.
- The weights and detailed implementation remain private.

UI/API-only Release (Hosted)

- Only an **inference service** is provided.
- The weights and detailed implementation remain private.
- Example: OpenAl's generally available models like GPT-4 and beyond [6].

Architecture + Checkpoint Release

Weights are distributed as Open Weights.

- Weights are distributed as Open Weights.
- This allows for local execution or use as a starting point for retraining.

- Weights are distributed as Open Weights.
- This allows for local execution or use as a starting point for retraining.
- Examples: Mistral 7B (Apache 2.0) [10], DeepSeek-R1 (MIT) [11].

- Weights are distributed as Open Weights.
- This allows for local execution or use as a starting point for retraining.
- Examples: Mistral 7B (Apache 2.0) [10], DeepSeek-R1 (MIT) [11].
- The training data and complete training procedures are often not disclosed.

Release of Training Code and Recipes

Release of Training Code and Recipes

Some initiatives also release data pipelines and training scripts.

Release of Training Code and Recipes

- Some initiatives also release data pipelines and training scripts.
- This is done to improve training reproducibility.

Release of Training Code and Recipes

- Some initiatives also release data pipelines and training scripts.
- This is done to improve training reproducibility.
- Example: Al2's OLMo project [13].

License Basics (For Source Code)

5. License Basics (For Source Code)

Here, we summarize four widely used Open Source Software (OSS) licenses.

5. License Basics (For Source Code)

Here, we summarize four widely used Open Source Software (OSS) licenses.

The focus is on their **practical implications**.

5. License Basics (For Source Code)

Here, we summarize four widely used Open Source Software (OSS) licenses.

The focus is on their **practical implications**.

Remark (Disclaimer)

Final determination of "can I use this?" must be based on the **specific license text and its scope**.

This license is **very permissive**, with minimal conditions.

• Conditions for users: Include the original copyright notice and permission notice in copies or derivative works.

- Conditions for users: Include the original copyright notice and permission notice in copies or derivative works.
- **Permissions for users**: "Without restriction." Commercial use is permitted.

- Conditions for users: Include the original copyright notice and permission notice in copies or derivative works.
- **Permissions for users**: "Without restriction." Commercial use is permitted.
- Warranty and Liability: No warranty and no liability for the authors.

- Conditions for users: Include the original copyright notice and permission notice in copies or derivative works.
- **Permissions for users**: "Without restriction." Commercial use is permitted.
- Warranty and Liability: No warranty and no liability for the authors.
- Model examples: DeepSeek-v3, DeepSeek-R1 [11].

Similar to MIT, this license is **highly permissive**.

Similar to MIT, this license is **highly permissive**.

Similar to MIT, this license is **highly permissive**.

It includes a clause prohibiting the use of developers' or contributors' names for endorsement without permission [14].

• Conditions for users: Include notices; do not use names for promotion.

Similar to MIT, this license is **highly permissive**.

- Conditions for users: Include notices; do not use names for promotion.
- **Permissions for users**: Essentially unrestricted, including commercial use.

Similar to MIT, this license is **highly permissive**.

- Conditions for users: Include notices; do not use names for promotion.
- Permissions for users: Essentially unrestricted, including commercial use.
- Warranty and Liability: No warranty and no liability.

Similar to MIT, this license is **highly permissive**.

- Conditions for users: Include notices; do not use names for promotion.
- **Permissions for users**: Essentially unrestricted, including commercial use.
- Warranty and Liability: No warranty and no liability.
- Model/Library example: The classic machine learning library scikit-learn [15].

This license grants users freedoms similar to the MIT License.

This license grants users freedoms similar to the MIT License.

It has the added benefit for users of an explicit grant of patent licenses [16].

This license grants users freedoms similar to the MIT License.

It has the added benefit for users of an explicit grant of patent licenses [16].

 Conditions for users: Include notices. If you modify files, you must state that.

This license grants users freedoms similar to the MIT License.

It has the added benefit for users of an explicit grant of patent licenses [16].

- Conditions for users: Include notices. If you modify files, you must state that.
- Permissions for users: Broad permissions, including commercial use.
 Explicit patent grant.

This license grants users freedoms similar to the MIT License.

It has the added benefit for users of an explicit grant of patent licenses [16].

- Conditions for users: Include notices. If you modify files, you must state that.
- Permissions for users: Broad permissions, including commercial use.
 Explicit patent grant.
- Model examples: Mistral 7B [10], Hugging Face Transformers library [17].

The GPL (GNU General Public License) embodies the philosophy of Copyleft.

The GPL (GNU General Public License) embodies the philosophy of Copyleft.

Copyleft: While allowing free use, modification, and redistribution, it **obligates** derivative works to be under the same license.

The GPL (GNU General Public License) embodies the philosophy of Copyleft.

Copyleft: While allowing free use, modification, and redistribution, it **obligates** derivative works to be under the same license.

This aims to ensure that the freedom of the software is perpetually inherited.

 GPLv3: Has a strong copyleft provision. If you distribute software containing GPLv3 code, the source code of the entire software must be released under GPLv3 [18].

- GPLv3: Has a strong copyleft provision. If you distribute software containing GPLv3 code, the source code of the entire software must be released under GPLv3 [18].
- AGPL-3: A variant that closes the "server-side loophole." The source code disclosure obligation is triggered even if the software is just used to provide a service over a network, without being distributed.

- GPLv3: Has a strong copyleft provision. If you distribute software containing GPLv3 code, the source code of the entire software must be released under GPLv3 [18].
- AGPL-3: A variant that closes the "server-side loophole." The source code disclosure obligation is triggered even if the software is just used to provide a service over a network, without being distributed.
- Model Example: YOLOv5 uses AGPL-3.0 [19].

Practical Implications of Copyleft Licenses:

Practical Implications of Copyleft Licenses:

• They impose strong restrictions on integration into services and mixing with other code.

Practical Implications of Copyleft Licenses:

- They impose strong restrictions on integration into services and mixing with other code.
- This can lead to unintended requirements to disclose your own source code.

Practical Implications of Copyleft Licenses:

- They impose strong restrictions on integration into services and mixing with other code.
- This can lead to unintended requirements to disclose your own source code.
- Careful consideration is required, especially for commercial use.

What if source code or a model has **no license** specified?

What if source code or a model has **no license** specified?

Remark (Be cautious for "no license" situations)

If no license is specified, it is understood by **default that all rights are reserved**.

What if source code or a model has no license specified?

Remark (Be cautious for "no license" situations)

If no license is specified, it is understood by **default that all rights are reserved**.

• You have **no permission** for use, modification, or redistribution [1, 2].

What if source code or a model has no license specified?

Remark (Be cautious for "no license" situations)

If no license is specified, it is understood by **default that all rights are reserved**.

- You have **no permission** for use, modification, or redistribution [1, 2].
- Such materials should be avoided.

(Open-Weight Type)

6. Model-Specific Licenses (Open-Weight Type)

Recent open-weight models sometimes use custom terms that are not standard OSS licenses.

6. Model-Specific Licenses (Open-Weight Type)

Recent open-weight models sometimes use custom terms that are not standard OSS licenses.

These often include use restrictions or thresholds based on Monthly Active Users (MAU).

Example (Llama series (Meta))

The Community License for the Llama 3 series allows commercial use with restrictions [8, 20].

Example (Llama series (Meta))

The **Community License** for the Llama 3 series allows **commercial use with restrictions** [8, 20].

• The terms are subject to conditions on scale and application.

Example (Llama series (Meta))

The Community License for the Llama 3 series allows commercial use with restrictions [8, 20].

- The terms are subject to conditions on scale and application.
- The 700 million MAU threshold clause is well-known for Llama 2 and 3.

Example (Qwen 2.5 (Alibaba))

The license for the Qwen series can vary even within the same version family.

Example (Qwen 2.5 (Alibaba))

The license for the Qwen series can vary even within the same version family.

 The largest models (e.g., Qwen2.5-72B-Instruct) used a custom Qianwen License with a 100 million MAU threshold [9].

Example (Qwen 2.5 (Alibaba))

The license for the Qwen series can vary even within the same version family.

- The largest models (e.g., Qwen2.5-72B-Instruct) used a custom Qianwen License with a 100 million MAU threshold [9].
- However, smaller models in the same series (e.g., Qwen2.5-7B-Instruct) are licensed under the standard Apache License 2.0.

Example (Qwen 2.5 (Alibaba))

The license for the Qwen series can vary even within the same version family.

- The largest models (e.g., Qwen2.5-72B-Instruct) used a custom Qianwen License with a 100 million MAU threshold [9].
- However, smaller models in the same series (e.g., Qwen2.5-7B-Instruct) are licensed under the standard Apache License 2.0.
- Later versions, like Qwen 3, seem to have standardized on Apache 2.0.

The **CreativeML Open RAIL-M** license is used by image generation Als like **Stable Diffusion** [21].

The CreativeML Open RAIL-M license is used by image generation Als like Stable Diffusion [21].

RAIL stands for Responsible Al License.

The **CreativeML Open RAIL-M** license is used by image generation Als like **Stable Diffusion** [21].

RAIL stands for Responsible Al License.

It permits free use, modification, and distribution, but imposes **explicit Use Restrictions**.

The license includes clauses that prohibit use for purposes such as:

- Illegal purposes
- Generating content intended to harm or exploit others
- Spreading misinformation or disinformation
- Uses that violate individual privacy

The license includes clauses that prohibit use for purposes such as:

- Illegal purposes
- Generating content intended to harm or exploit others
- Spreading misinformation or disinformation
- Uses that violate individual privacy

It also requires that when distributing **derivative works**, the **same use restrictions must be imposed on downstream users**.

6.2 Creative Commons

While **CC licenses** are widely used for documents, images, and data, they are generally **unsuitable for software/models**.

6.2 Creative Commons

While **CC licenses** are widely used for documents, images, and data, they are generally **unsuitable for software/models**.

• They were not designed with source code and executable programs in mind.

6.2 Creative Commons

While **CC licenses** are widely used for documents, images, and data, they are generally **unsuitable for software/models**.

- They were not designed with source code and executable programs in mind.
- Key variations include:
 - CC BY 4.0 (Attribution) [22]
 - CC BY-SA 4.0 (ShareAlike) [23]
 - CC BY-NC 4.0 (NonCommercial) [24]

Case Study: Separation of Rights

Holders

It is crucial to understand that the license for the **code** and the license for the **weights** can be different.

It is crucial to understand that the license for the **code** and the license for the **weights** can be different.

Example

The Hugging Face **Transformers** library is under the permissive Apache 2.0 license [17].

It is crucial to understand that the license for the **code** and the license for the **weights** can be different.

Example

The Hugging Face **Transformers** library is under the permissive Apache 2.0 license [17].

However, the **license for each checkpoint** you download to use with that library is **separate**.

Rights and conditions differ for each set of weights.

Rights and conditions differ for each set of weights.

You must check the model card and LICENSE file for each specific model [7].

Rights and conditions differ for each set of weights.

You must check the model card and LICENSE file for each specific model [7].

For example, within the same Transformers framework:

- DeepSeek-R1 weights are MIT [11].
- The Mistral family is Apache 2.0 [10].
- The **Llama** family has its own custom license [8, 9].

Model Versions and License

Differences Across Versions

Companies often release multiple models under the same series name.

Companies often release multiple models under the same series name.

However, there is **no guarantee** that the licenses for all models in a series will be the same.

Companies often release multiple models under the same series name.

However, there is **no guarantee** that the licenses for all models in a series will be the same.

Example (Qwen 2.5 (Alibaba))

As we saw, different models in the Qwen 2.5 series had different licenses (custom vs. Apache 2.0) [9]. You must check the license for the <u>specific model</u> you wish to use.

You might be curious about names like "Qwen2.5-72B-Instruct".

You might be curious about names like "Qwen2.5-72B-Instruct".

While this course avoids deep dives into specific models, a brief explanation is useful. Models in a series typically differ in:

• Scale: The number of parameters (e.g., 7B vs 72B).

You might be curious about names like "Qwen2.5-72B-Instruct".

While this course avoids deep dives into specific models, a brief explanation is useful. Models in a series typically differ in:

- Scale: The number of parameters (e.g., 7B vs 72B).
- **Fine-tuning**: Whether it's a base model or tuned for a specific task (e.g., "Instruct").

The scale of a model is expressed by the **total number of real numbers in its checkpoint (parameters)**.

The scale of a model is expressed by the **total number of real numbers in its checkpoint (parameters)**.

"7B" means the checkpoint contains approximately 7 billion (7 \times 10 9) parameters.

The scale of a model is expressed by the total number of real numbers in its checkpoint (parameters).

"7B" means the checkpoint contains approximately 7 billion (7 \times 10 9) parameters.

In mathematical terms, the parameters (checkpoint) are a real vector:

$$\boldsymbol{\theta} = (\theta_1, \theta_2, \dots, \theta_D) \in \mathbb{R}^D.$$

A "7B model" means the dimension $\mathcal D$ of this vector is approximately 7 billion.

The scale of a model is expressed by the total number of real numbers in its checkpoint (parameters).

"7B" means the checkpoint contains approximately 7 billion (7 \times 10⁹) parameters.

In mathematical terms, the parameters (checkpoint) are a real vector:

$$\boldsymbol{\theta} = (\theta_1, \theta_2, \dots, \theta_D) \in \mathbb{R}^D.$$

A "7B model" means the dimension D of this vector is approximately 7 billion.

Generally, a higher parameter count increases expressive power but also computational cost.

Each parameter θ_i is stored on a computer in a specific numerical format. This affects the model's file size and inference speed.

Each parameter θ_i is stored on a computer in a specific numerical format. This affects the model's file size and inference speed.

Common formats include:

• fp32 (single-precision): 32 bits. High precision, large memory. A 7B fp32 model needs about $7 \times 4 = 28$ GB.

Each parameter θ_i is stored on a computer in a specific numerical format. This affects the model's file size and inference speed.

Common formats include:

- fp32 (single-precision): 32 bits. High precision, large memory. A 7B fp32 model needs about $7 \times 4 = 28$ GB.
- fp16 (half-precision): 16 bits. Halves memory usage, but has a smaller dynamic range.

Each parameter θ_i is stored on a computer in a specific numerical format. This affects the model's file size and inference speed.

Common formats include:

- fp32 (single-precision): 32 bits. High precision, large memory. A 7B fp32 model needs about $7 \times 4 = 28$ GB.
- fp16 (half-precision): 16 bits. Halves memory usage, but has a smaller dynamic range.
- **bf16** (**Bfloat16**): 16 bits. Wide dynamic range like fp32, but lower precision than fp16. Good for training stability [25].

Each parameter θ_i is stored on a computer in a specific numerical format. This affects the model's file size and inference speed.

Common formats include:

- fp32 (single-precision): 32 bits. High precision, large memory. A 7B fp32 model needs about $7 \times 4 = 28$ GB.
- fp16 (half-precision): 16 bits. Halves memory usage, but has a smaller dynamic range.
- **bf16** (**Bfloat16**): 16 bits. Wide dynamic range like fp32, but lower precision than fp16. Good for training stability [25].
- Quantization: Using even fewer bits (e.g., int8, int4). Drastically reduces size and speeds up inference, often with a small accuracy drop.

9.2.1 Precise Definition of Floating-Point Numbers

The standard for floating-point numbers is **IEEE 754**. A number is represented by three parts: a **Sign**, an **Exponent**, and a **Mantissa/Fraction**.

9.2.1 Precise Definition of Floating-Point Numbers

The standard for floating-point numbers is **IEEE 754**. A number is represented by three parts: a **Sign**, an **Exponent**, and a **Mantissa/Fraction**.

A value V is defined as:

$$V = (-1)^S \times (1.M)_2 \times 2^{E-\mathrm{bias}}$$

9.2.1 Precise Definition of Floating-Point Numbers

The standard for floating-point numbers is **IEEE 754**. A number is represented by three parts: a **Sign**, an **Exponent**, and a **Mantissa/Fraction**.

A value *V* is defined as:

$$V = (-1)^S \times (1.M)_2 \times 2^{E-\mathsf{bias}}$$

 Table 1: Bit Allocation for Floating-Point Formats

Format	Total Bits	Sign	Exponent	Mantissa	Bias
fp32	32	1	8	23	127
fp16	16	1	5	10	15
bf16	16	1	8	7	127

Although both are 16-bit formats, their characteristics differ significantly.

Although both are 16-bit formats, their characteristics differ significantly.

fp16: Longer mantissa (10 bits)

 high precision. Shorter exponent (5 bits)
 arrow dynamic range. Prone to overflow or underflow.

Although both are 16-bit formats, their characteristics differ significantly.

- fp16: Longer mantissa (10 bits)

 high precision. Shorter exponent (5 bits)

 narrow dynamic range. Prone to overflow or underflow.
- bf16: Longer exponent (8 bits)
 wide dynamic range (same as fp32).
 Shorter mantissa (7 bits)
 lower precision.

Example (A number representable in bf16 but not in fp16)

Large number: Consider V = 100,000.

Example (A number representable in bf16 but not in fp16)

Large number: Consider V = 100,000.

• fp16: The maximum representable value is 65,504. Therefore, 100,000 overflows to infinity (∞).

Example (A number representable in bf16 but not in fp16)

Large number: Consider V = 100,000.

- **fp16**: The maximum representable value is 65,504. Therefore, 100,000 **overflows** to infinity (∞).
- **bf16**: Has the same dynamic range as fp32. It can be **represented without issue**.

Example (A number representable in fp16 but not in bf16)

A number requiring precision: Consider $V=1+2^{-8}=1.00390625$. In binary, this is $(1.00000001)_2$.

Example (A number representable in fp16 but not in bf16)

A number requiring precision: Consider $V=1+2^{-8}=1.00390625.$ In binary, this is $(1.00000001)_2.$

• fp16: The mantissa has 10 bits. It can accurately represent the '1' in the 8th decimal place.

Example (A number representable in fp16 but not in bf16)

A number requiring precision: Consider $V=1+2^{-8}=1.00390625$. In binary, this is $(1.00000001)_2$.

- fp16: The mantissa has 10 bits. It can accurately represent the '1' in the 8th decimal place.
- **bf16**: The mantissa has only 7 bits. The 8th bit does not fit and is rounded. It cannot distinguish between 1 and $1 + 2^{-8}$.

Suffixes like "Instruct" or "Chat" suggest the model has undergone **Instruction Finetuning**.

Suffixes like "Instruct" or "Chat" suggest the model has undergone **Instruction Finetuning**.

 A base large language model (foundation model) is trained to predict the next word.

Suffixes like "Instruct" or "Chat" suggest the model has undergone **Instruction Finetuning**.

- A base large language model (foundation model) is trained to predict the next word.
- Additional fine-tuning is performed using a dataset of "instruction (prompt) and desired response" pairs [26].

Suffixes like "Instruct" or "Chat" suggest the model has undergone **Instruction Finetuning**.

- A base large language model (foundation model) is trained to predict the next word.
- Additional fine-tuning is performed using a dataset of "instruction (prompt) and desired response" pairs [26].
- This teaches the model to be a helpful assistant, follow diverse instructions, and engage in conversation.

• "Open" does not mean free to use: The license text governs everything.

Always check the LICENSE and Terms of Service on the model page.

- "Open" does not mean free to use: The license text governs everything.

 Always check the LICENSE and Terms of Service on the model page.
- Apache 2.0 is a safe choice: If you want your model to be widely used but have little commercial intent, Apache 2.0 is easy to handle due to the clarity of its patent clauses [16].

- "Open" does not mean free to use: The license text governs everything.
 Always check the LICENSE and Terms of Service on the model page.
- Apache 2.0 is a safe choice: If you want your model to be widely used but have little commercial intent, Apache 2.0 is easy to handle due to the clarity of its patent clauses [16].
- The legal nature of checkpoints is an immature area: It is reasonable to consider them as having aspects of both source code and data. No legal consensus has been established [27, 28].

- "Open" does not mean free to use: The license text governs everything.

 Always check the LICENSE and Terms of Service on the model page.
- Apache 2.0 is a safe choice: If you want your model to be widely used but have little commercial intent, Apache 2.0 is easy to handle due to the clarity of its patent clauses [16].
- The legal nature of checkpoints is an immature area: It is reasonable to consider them as having aspects of both source code and data. No legal consensus has been established [27, 28].
- A policy of "when in doubt, do not use" is the safest approach.

Summary

11. Summary

 Many "open models" release their architecture and checkpoints, but the training data and learning algorithms are often kept private.

11. Summary

- Many "open models" release their architecture and checkpoints, but the training data and learning algorithms are often kept private.
- Even if a model is "public," whether third parties can freely use it is determined by its license.

11. Summary

- Many "open models" release their architecture and checkpoints, but the training data and learning algorithms are often kept private.
- Even if a model is "public," whether third parties can freely use it is determined by its license.
- In practice, one must understand the nature of licenses like MIT / BSD-3 / Apache 2.0 / GPL-3 and always check the LICENSE and model card for each model.

Next Time

12. Next Time

Next time, we will download and run a specific open large language model locally.

12. Next Time

Next time, we will download and run a specific open large language model locally.

This hands-on exercise will confirm the division of roles between:

• The **neural network part** (architecture + checkpoint).

12. Next Time

Next time, we will download and run a specific open large language model locally.

This hands-on exercise will confirm the division of roles between:

- The **neural network part** (architecture + checkpoint).
- The **surrounding components** (tokenizer, pre/post-processing, inference runtime).

Reference i

[1] GitHub Docs.

Licensing a repository.

https://docs.github.com/articles/licensing-a-repository.

[2] Choose a License.

No license.

https://choosealicense.com/no-permission/.

[3] Open Source Guides.

The legal side of open source.

https://opensource.guide/legal/.

Reference ii

[4] OpenAl.

Better language models and their implications.

https://openai.com/index/better-language-models/, 2019.

[5] OpenAl.

Releasing gpt-2: 1.5b release.

https://openai.com/index/gpt-2-1-5b-release/, 2019.

[6] OpenAl.

Models.

https://platform.openai.com/docs/models, 2025.

Reference iii

[7] Hugging Face Docs.

Licenses (hub).

https://huggingface.co/docs/hub/en/repositories-licenses, 2025.

[8] Meta.

Llama community license.

https://ai.meta.com/llama/license/, 2023-2024.

[9] Alibaba Cloud.

Qwen license agreement (e.g., qwen2.5-72b-instruct).

https:

//huggingface.co/Qwen/Qwen2.5-72B-Instruct/blob/main/LICENSE, 2024-2025.

Reference iv

[10] Mistral Al.

Announcing mistral 7b.

https://mistral.ai/news/announcing-mistral-7b/, 2023.

[11] DeepSeek-Al.

deepseek-ai/deepseek-r1.

https://huggingface.co/deepseek-ai/DeepSeek-R1/blob/main/LICENSE, 2025.

LICENSE: MIT.

[12] Hugging Face Docs.

Downloading models.

https://huggingface.co/docs/hub/en/models-downloading, 2025.

Reference v

[13] Al2.

Olmo: An open language model.

https://allenai.org/olmo, 2024-2025.

[14] Open Source Initiative.

The bsd 3-clause license.

https://opensource.org/license/bsd-3-clause/.

[15] scikit-learn.

License.

https://github.com/scikit-learn/scikit-learn/blob/main/COPYING.

Reference vi

[16] Apache Software Foundation.

Apache license, version 2.0.

http://www.apache.org/licenses/LICENSE-2.0.

[17] Hugging Face.

Transformers (license: Apache-2.0).

https://github.com/huggingface/transformers.

[18] Free Software Foundation.

Gnu general public license, version 3.

https://www.gnu.org/licenses/gpl-3.0.en.html.

Reference vii

[19] Ultralytics.

yolov5 (license: Agpl-3.0).

https://github.com/ultralytics/yolov5/blob/master/LICENSE.

[20] Meta AI.

Introducing meta llama 3.

https://ai.meta.com/blog/meta-llama-3/, 2024.

[21] CompVis and Stability AI.

Creativeml open rail-m.

https://huggingface.co/spaces/CompVis/stable-diffusion-license/raw/main/license.txt, 2022.

Reference viii

[22] Creative Commons.

Attribution 4.0 international (cc by 4.0).

https://creativecommons.org/licenses/by/4.0/.

[23] Creative Commons.

Attribution-sharealike 4.0 international (cc by-sa 4.0).

https://creativecommons.org/licenses/by-sa/4.0/.

[24] Creative Commons.

Attribution-noncommercial 4.0 international (cc by-nc 4.0).

https://creativecommons.org/licenses/by-nc/4.0/.

Reference ix

[25] D. Kalamkar et al.

Bfloat16: The secret to high performance on cloud tpus.

https://cloud.google.com/blog/products/ai-machine-learning/bfloat16-the-secret-to-high-performance-on-cloud-tpus, 2019.

[26] Jason Wei et al.

Finetuned language models are zero-shot learners.

<u>arXiv preprint arXiv:2109.01652</u>, 2022. ICLR 2022.

[27] Open Source Initiative.

Drafts of the open source ai definition.

https://opensource.org/ai/drafts, 2024-2025.

Reference x

[28] All Things Open.

The open source ai definition: Why we need it.

https://allthingsopen.org/articles/the-open-source-ai-definition-why-we-need-it, 2024.